



Analogue KNZD-15 Corrosion proof Phone

DESCRIPTION ITEM NO.:ZD0150012


1. Stainless steel 304 body, easy installation.
2. Waterproof rating IP66 dust proof.
3. Hands-free, built-in 0.5W loudspeaker.
4. Service temperature range from -30 degree to +75 degree.
5. Lightening protection to ITU-T recommendation K.21.
6. Flat metal keypad keep waterproof and dusty proof.
7. Flush mounted type installation
8. Auto release the line if the other side ends the call. This function upon buyer's requirement.
9. Can wipe with IPA, medicinal liquid.
10. Body in electrophoresis process finish no fingerprint, resistant to corrosion.
11. Telephone line powered.
11. Application: Clean room, pharmaceutical factory, hospital, chemical plant, metro etc.



SPECIFICATION

1. PSTN analogue telephone
2. DTMF dialing
3. MTBF: 100000 hours
4. MTTR: 2 hours
5. Connection: RJ11 screw terminal pair cable
6. Applicable for various types of SPC exchange PABX and dispatching exchange system with feeding voltage of 33-60V.
7. Ambient temperature: -30 ~ +60 degree. Relative humidity: 10%~95%
Atmospheric pressure: 86~106Kpa Circumstance noise: less than 60dB(A)
8. Sound level of ringing: over 70dB(A).
9. Standard frequency: low frequency group: 697. 770. 852. 941Hz,
high frequency group: 1209. 1336. 1477Hz, frequency deviation: -1.5% ~ +1.5%
10. Call transmission index: (5KM)SLR<12, RLR<-1, STMR>10, output impedance is 600 Ohm.
maximum distance: 7KM
11. Super strong function is available for free dialing (maximum length of each number is 16 digits).
12. Connection: RJ11 screw terminal pair cable (or RJ11 Socket of plug upon request)
with stainless steel cable protected

INSTALLATION



CERTIFICATION

EN55022: emissions

EN55024: immunity

Ingress Protection: GB4208-93 IP66 FCC

ITU-T Recommendations K21

EMC: EN50121 (Railway application-Electromagnetic Compatibility)



RoHS

PACKING



Unit size: 250*150*43mm Unit N.W: 1.25KG

1pcs packing box size: 325 *235 *165mm Unit N.W: 1.25KG Unit G.W: 1.75KG

14pcs in 1 outer Carton box: size: 730*390*340mm N.W: 17.5KG G.W: 23.7KG