



ITEM NO. G2000

IP Version Emergency Phone Box

DESCRIPTION

1. Body and all function have Self-diagnosis and report every 24 hours.
2. Built in Surge protection device for power supply and date.
3. Handset free super clear communication and surroundings noise reduction.
4. Heavy duty Vandal resistant enclosure and call buttons.
5. With or without keypad optional
6. Remote configuration and upgrading
7. Waterproof grade about IP65
8. Body with grounding connection protection
9. Support hotline call, self stop if the other side hang up.
10. Built-in loud speaker 8W. noise canceling microphone.
11. AC 110v/220v powered or built-in rechargeable battery with solar powered panel optional
12. The design is super thin and smart. Embed style and hanging style can be chosen.
13. Colours: RED enclosure + Stainless steel. Color and style can be customized.



SPECIFICATION

Built-in Loud speaker: 8W with amplifier.

Ringling: Through internal Speaker/ringer.

Power Supply: Re-chargeable Battery powered: 11.1V/14Ah, Solar back-up: 18V/40W

stand-by time : 27.6 Hours

continuous talk time : 13 Hours

charging time : 4.5 Hours

Built-in battery Standby: 3 days

Built-in battery talking time: 18 hours

Auxiliary Contacts:1 Aux Output, dry contact

Contact Ratings. Load: Resistive load

Rated load:0.3 A at 125 VAC; 1 A at 30 VDC

Rated carry current:1A

Audio Codes:G.711, G.722, G.729

Network:10/100 BaseTX Ethernet, RJ45 connectors, Cat5e or better

IP Protocols:IPv4, TCP, UDP, DHCP, SIP

LAN Protocols:Power over Ethernet(PoE,802.3af), WLAN(IEEE 802.3af), Network Access

Control(IEEE 802.1x),STP(IEEE 802.1d), RSTP(IEEE 802.1d-2004)

Programming:Non-volatile flash memory programming and configuration through Web GUI

Management and Operation:DHCP and static IP, remote automatic software upgrade, centralized monitoring.

Echo cancellation code:G.167/G.168

Environment conditions:

Ambient temperature: -25°C to 70°C. Relative humidity:10%~95%

Atmospheric pressure: 86~106Kpa Circumstance noise:less than 60dB(A)

Impact protection: IK 09 according to EN50102

CERTIFICATION



RCM: AS/NZS CISPR 32

Australian communications:AS/CA S004

Australian Equipment-safety: AS/NZS 60950.1:2015

EMC: EN50121(Railway application-Electromagnetic Compatibility)

PACKAGING

Telephone Unit size: 2200*310*255mm Unit Net weight: 90kg

2pcs in a wooden box CTN box, size: 35X80X255 G.W: 186kg

20GP: 88PCS 40GP: 176PCS 40HQ: 205PCS





